



**6711 Power Inn Rd, Suite B, Sacramento, CA 95828**  
**(916) 957-5900 | [sales@alphaelevatorcontrol.com](mailto:sales@alphaelevatorcontrol.com)**

Job Name: \_\_\_\_\_  
 Company/Branch: \_\_\_\_\_  
 Contact Name: \_\_\_\_\_  
 Phone #: \_\_\_\_\_  
 Email: \_\_\_\_\_

|               |                            |     |     |     |              |
|---------------|----------------------------|-----|-----|-----|--------------|
| 3PH (default) | <b>*Main Line Voltage:</b> | 208 | 240 | 480 | Other: _____ |
| 1PH           | Motor Volts:               | 208 | 240 | 480 | Other: _____ |
|               | Door Operator Model:       |     |     |     |              |

Hoistway Cable (ft):

[illegible]

\*\*Lengths required if needed

|                   |               |          |           |          |     |
|-------------------|---------------|----------|-----------|----------|-----|
| Drive Preference: | Machine Type: | Geared   | Location: | Overhead | MRL |
| Magnetek          | KEB           | Gearless |           | Basement |     |

- Harmonic Filter
- EMI Filter
- Line Reactor
- Interface-Earthquake

**Valve must be 110/115/120 VAC**

*Quoted as NEMA-1 unless otherwise specified*

Interface-Emergency Power  
Interface-Lobby Panel  
Hall Lanterns-CE  
Hall Lanterns-Alpha Boards

***Fixtures must be 24 VDC.***

## Rev 0.3 / 05-2024